

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 survey dated July 28, 1882 (DCSO rec. Vol. 19 Page 7896)

Set a sandstone 15x15x8 ins., 12" in ground, marked ¼ on N. face for the sec. cor., from which
A Fir 15" dia., bears N.23°E., 74 lks. dist., marked ¼ S BT.
A Laurel 14" dia., bears S.60°E., 24 lks. dist., marked ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell; Frank Jones and Joe Brady - May/June 1966 - C.S. File 54/25-10

Found - No trace of Laurel tree.
15" D.Fir, now stump, N.23°E., 48.8 ft bark scribed, not all there, curved part of "B" and "T".
Set stone at corner, approx. record size, no markings visible.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 5 W
¼ $\frac{S\ 24}{S\ 25}$
1966
New BTs -23" D.Fir N.43°E., 20.0 ft. mkd. ¼ S24 CS BT.
7" Cedar S.38°W., 32.4 ft. mkd. ¼ S25 CS BT.
This corner lies on East slope about 140.0 ft. from top of ridge.

Brass cap, 1 orig. BT, 2 County trees Fd. OK, BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15660)

Found OK, Feb. 1996 by G. Lang - M 127-73