

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 surveyed July 28, 1882 (DCSO rec. Vol. 19 Page 7898)

-----  
Set a Laurel post, 3 ft. long, 3" square, 18" in ground, marked  $\frac{1}{4}$  S on the North side for the  $\frac{1}{4}$  sec. cor., from which  
A Fir 16" dia., bears N.78°W., 138 lks. marked  $\frac{1}{4}$  S BT.  
A Fir 20" dia., bears S.45°W., 160 lks. marked  $\frac{1}{4}$  S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15662-63)

-----  
Point for the  $\frac{1}{4}$  sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  in. diam., 24 ins. in the ground, with brass cap mkd:  $\frac{1}{4}$   $\frac{S\ 13}{S\ 24}$   
T 31 S R 5 W  
1973

from which  
A Madrone 8" dia., bears N.3 $\frac{1}{2}$ °W., 24 lks. dist., mkd.  $\frac{1}{4}$  S13 BT.  
A Madrone 9" dia., bears S.8 $\frac{1}{2}$ °E., 27 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S24 BT.

Found OK, Feb. 1996 by G. Lang - M 127-73

Fd. & used on BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1861, surveyed Sept. 3, 1997 - (DCSO records Vol. 53 Page(s) 20263)