

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 456 surveyed July 28, 1882 (DCSO rec. Vol. 19 Page 7900)

Set a Laurel post, 4 ft. long, 3" square, 20" in ground, marked $\frac{1}{4}$ S on North face for the $\frac{1}{4}$ sec. cor., from which
A Fir 15" dia., bears S.30°W., 75 lks. dist. marked $\frac{1}{4}$ S BT.
A Laurel 12" dia., bears N.22°W., 71 lks. dist., marked $\frac{1}{4}$ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15665-66)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2½ ins. dia., 24 ins. in the ground, with brass cap mkd: $\frac{1}{4}$ $\frac{S\ 12}{S\ 13}$
T 31 S R 5 W
1973

from which
A Fir 20" dia., bears N.28°E., 44 lks. dist., mkd. $\frac{1}{4}$ S12 BT.
A Fir 14" dia., bears S.30°E., 25 lks. dist., marked $\frac{1}{4}$ S13 BT.

Found OK by B. Shaner, Oct. 2000 - M132-51