

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 25 & 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15642-43)

The sec. cor., perpetuated by Powell in 1966, monumented with an iron post, 1½" dia., firmly set, protruding 10" above ground with brass cap marked: County Surveyors Office

T 31 S R 4 W
S 25 | S 31
S 36 |
R 5 W |
1966

from which the remains of the original bearing trees:

A Fir snag 29" dia, bears N.50°E., 45 lks. dist., with healed blaze. (Marks reported destroyed by Bushey, in 1894)

A Fir 40" dia., bears S.32°E., 41 lks. dist., with healed blaze. (marks reported destroyed by Bushey in 1894)

A Fir snag 30" dia., bears S.36°W., 35 lks. dist., with healed blaze.

A Fir stump 30" dia., bears N.54°W., 31 lks. dist., with scribe marks BT visible on opened blaze.

and bearing trees mkd. by Powell:

A Cedar 16" dia., bears S.51°E., 77 lks. dist. with scribe marks T31S 4W 3 visible on partially healed blaze.

A Fir snag 52" dia., bears N.60°E., 75 lks. dist., with healed blaze.

and new bearing trees:

A Fir 4" dia., bears S.16°W., 10 lks. dist., mkd. X BT.

A Fir 6" dia., bears N.6°W., 30 lks. dist. mkd. T31S R5W S25 BT.

1966 County brass cap, 4 orig. BTs, 2 County BTs and 2 1972 BTs, Fd. OK, BLM survey by Rogers, McMullen and Bishop under Group #1217, 1984-86 (DCSO records, Vol. 47 Pg. 18134)