

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Butler Ives and Geo. Hyde under Contract #39 dated Jan. 4, 1854 (DCSO records Vol. 18 Page(s) 7780)

Set ¼ sec. post, on SE slope, from which
 A Laurel 12" dia., bears N.15°E., 13 lks.
 A Laurel 3" dia., bears S.58°W., 23 lks.

GLO survey by Wm. M. Bushy, under Contract #620 dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7859)

The ¼ sec. cor. is gone. I find 1 witness tree.
At cor. point
Set a stone, 15x6x6 ins., 10" in the ground, for ¼ sec. cor. marked ¼ on W face; from which
 A Laurel 12" dia., (16" now) bears N.15°E., 13 lks. dist., marked ¼ S BT.
I find no trace of the other witness tree. I therefore mark
 A Laurel 5" dia., which bears S.65°W., 34 lks. dist., marked ¼ S BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15644)

Point for the ¼ sec. cor. of sec. 25 only, determined by the method of irregular boundaries, there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
 ¼ S 25
 T 31 S
 R 5 W
 1973
from which
 A Fir 25" dia., bears S.36°W., 63 lks. dist. mkd ¼ S25 BT.
 A Fir 20" dia., bears N.38°W., 31 lks. dist. mkd ¼ S25 BT.

Corner Fd. OK, BLM survey by Rogers, McMullen and Bishop under Group #1217, Surveyed 1984/1986 (DCSO records, Vol. 47 Page 18135)