

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E 1/4 cor. for Sec. 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Ives and Hyde under Contract #39 dated Jan. 4, 1854 (DCSO records Vol. 18 Page(s) 7779)

Set ¼ sec. post, from which
A Fir 13" dia., bears S.75°W., 38 lks.
A Maple 5" dia., bears S.66°E., 8 lks.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15646)

Point for the ¼ sec. cor. of sec. 24 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 23" in the ground, with brass cap marked:
¼ S 24
T 31 S
R 5 W
1973

from which
A Hemlock 10" dia., bears S.68½°W., 43½ lks. dist., marked ¼ S24 BT.
A Fir 8" di., bears N.6½°W., 47 lks. dist., marked ¼ S24 BT.

Found OK, Feb. 1996 by G. Lang - M 127-73