

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 700446

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 18 only, T31-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Robert M. Thompson - For: Sunny Valley Lumber Co.
-July 12, 1959 - M 15-24

Old corner not found.
I Set 3/4" Iron pipe 30", 24" in ground.
Scribed - 13" D.Fir N.46½°E., 52.2 ft.
12" D.Fir S.24½°E., 25.3 ft.

Douglas Co. Surveyors Office - John Powell, Frank Jones, Joe
Brady - March 1966 - C.S. File 54/20-39

Found - Iron pipe at ¼ cor.
13" D.Fir now 14", N.46½°E., 52.2 ft. scribe visible
"S18", rest pitched over.
12" D.Fir now 16", S.24½°E., 25.3 ft., good scars.
(Both distances to the face of trees)
Set Brass cap at ¼ cor. marked: County Surveyors Office

R	T31S	R
5	¼ S 18	4
W		W
1966		

Bearing trees in good condition. I. Pipe rusty.

1966 Brass cap and 2 BTs, Fd. OK by BLM resurvey by Daniel
Berry and Charles Akin under Group #800, surveyed, Sept.
1972/June 1973 (DCSO records Vol. 38 Page(s) 15648)

Kris DeGroot - For: Silver Butte Timber - 3/2005 - M 146-19

I did not accept Thompson's monuments at the W ¼ corner & the
N 1/16 corner of section 18 only because they were set at
proportionate distance between the NW and SW closing corners
and not on the east line of Sec. 13.

Set - 5/8"x30" iron rod 24" in the ground with a 2" dia.
alum. cap stamped: T31S

R5W R4W

¼

|18

2005

PLS 1941

From which new bearing trees:

A 12" D.Fir bears S.20°E., 43.4 ft scribed "¼ S18 BT".

A 7" D.Fir bears N.70½°E., 35.9 ft scribed "¼ S18 BT".

And a reference monument:

A 1¼" (O.D.) iron pipe by DCSO in 1966, firmly set,
projecting 18 " above the ground bears S.89°14'13" W.

5.75 ft with a 2½" brass cap stamped:

continued next page

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 700446

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 18 only, T31-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

COUNTY SURVEYORS OFFICE

T31S	R4W
R	R
5 ¼	S 18 4
W	W

1966

From which reference monument BTs by Thompson in 1959:
A 30" cedar bears N.46°E., 52.5 ft with a healed blaze
(rec N.46½°E., 52.2 ft)
A 33" D.Fir bears S.24°E., 26.2 ft with a healed blaze
(rec S.24½°E., 25.3 ft)
And Thompson's 1959 monument:
A ¾" iron pipe bears North, 0.3 ft.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 3/28/2005 - C.S. File 67/10-16

Cut 1966 brass cap off of pipe, put yellow plastic cap
stamped "CO SURVEYOR" in end of pipe, see M146-19