

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Butler Ives and Geo. Hyde, under Contract #39,
dated Jan. 4, 1854 (DCSO records Vol. 14 Page(s) 7777)

Set ¼ sec. post, on E slope of mountain, from which
A Fir 5" dia., bears S.10°E., 34 lks.
A Redwood 12" dia., bears S.22°W., 89 lks.

BLM resurvey by Daniel Berry and Charles Akin, under Group
#800. Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38
Page(s) 15651-52)

Point for the ¼ sec. cor. of sec. 1 only, at proportionate
distance; there is no remaining evidence of the original
corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the
ground, with brass cap mkd:

¼ S 1
T 31 S
R 5 W
1973

from which

A Fir 8" dia., bears S.71°W., 44 lks. dist., mkd. ¼ S1 BT.
A Fir 23" dia., bears N.23°W., 43½ lks. dist., mkd. ¼ S1
BT.