

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 931020

PRIMARY CORNER DESCRIPTION S Cor. MS 794 (Cor. #3 Skookum)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Horace G. Hall, U.S. Mineral Surveyor under Instructions dated Aug. 9, 1916 (DCSO records Vol. 29 Page(s) 12216)

-----  
Cor. #3

A Cedar post 5" sq., 4½ ft. long, set 2 ft. in the ground, with mound of earth and stones, scribed 3-794; whence

A Fir 12" dia., blazed and scribed 3-794 B.T. bears N.87°00'E., 17.7 ft.

-----  
BLM Corrective Resurvey - John Jelley, Lynn Roseberry, Floyd Brooks, Under Group #s 320 and 614, - Surveyed June 1966 through May 1968. (DCSO records Vol. 35 Page(s) 14382)

-----  
Cor. No. 3 Skookum Lode, restored by the method of broken boundaries, there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. dia., 24 ins. in the ground, with brass cap mkd:

SK  
3-794 /  
  \ /  
S 5    \  
T 31 S R 5 W  
1968

from which

A Cedar 17" dia., bears N.57 3/4°E., 305 lks. dist., marked 3-794 BT.