

TOWNSHIP 31 RANGE 05 POINT IDENTIFIER # 931030

PRIMARY CORNER DESCRIPTION E Cor. MS 794 (Cor #2 Skookum)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Horace G. Hall, U.S. Mineral Surveyor surveyed under Instructions dated Aug. 9, 1916 (DCSO records Vol. 29 Page(s) 12216)

Cor. #2

A Cedar post, 5" sq., 4½ ft. long, set 2 ft. in the ground, with mound of earth and stones, scribed 2-794; whence

A Laurel 12" dia., blazed and scribed 2-794 B.T. bears N.81°16'W., 6.7 ft.

BLM Corrective Resurvey - John Jelley, Lynn Roseberry, Floyd Brooks, Under Group #s 320 and 614, - Surveyed June 1966 through May 1968. (DCSO records Vol. 35 Page(s) 14381)

Cor. #2, Skookum Lode, monumented with the burned original Cedar post, 5" sq., protruding 3 ft. above the ground, firmly set, from which the original bearing tree:

A burned Madrone snag 15" dia., bears S.81°16'W., 10 lks. dist., with scribe marks 2-794 SK visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. dia., 24 ins. in the ground, with brass cap mkd:

SK \ S 4
2-794 \
/
/
T 31 S R 5 W
1968

from which a new bearing tree

A Fir 15" dia., bears N.57°W., 195 lks. dist., mkd. 2-794 BT.

Deposit the wood post alongside the iron post.