

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T31-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7945)

Set post cor. to secs. 25, 30, 31 and 36, on summit of NE. slope of ridge, from which

- A Fir 3" dia., bears N.49°E., 26 lks. dist.
- A Fir 20" dia., bears S.14°E., 15 lks. dist.
- A Fir 18" dia., bears S.75°W., 7 lks. dist.
- Chinquapin 6" dia., bears N.40°W., 53 lks. dist.

W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7951-52)

Set a Laurel post, 4 ft. long, 4" sq., 24" in the ground mkd. T31S R6W S30 on NE. face; S31 on E. face; S36 on the SW. face; and R7W S25 on NW. face; also one notch on S. and five notches on the North angles of the same for the corner to Secs. 25, 30, 31 and 36, from which

- A Laurel 6" dia., bears N.20°E., 11 lks. dist. mkd. T31S R6W S30 BT.
- A Laurel 12" dia., bears S.18°E., 82 lks. dist., mkd. T31S R6W S31 BT.
- A Laurel 5" dia., bears S.34°W., 40 lks. dist. mkd. T31S R7W S36 BT.
- A Laurel 6" dia., bears N.66°W., 32 lks. dist. mkd. T31S R7W S25 BT.

Survey by Howard Johnstone - For: Roseburg Lumber Co. - Jan. 4, 1961 - C.S. File 51/163-4

Found - 6" Madrone N.66°W., 21.1 ft., scribe visible.
6" Madrone S.34°W., 26.4 ft., down.

Set 4" x 4" Cedar post.
New BTs - 20" D.Fir S.57°W., 32.5 ft.
8" D.Fir S.18°E., 24.0 ft.
16" D.Fir N.46½°W., 57.0 ft.
6" D.Fir N.78°E., 38.0 ft.

Douglas Co. Surveyors Office - John Powell, Frank Jones and Cliff Stone - Oct. 1966 - C.S. File 54/31-31

Found - 3/4" Iron pipe not recorded. (See M 33-49, Johnstone's survey)
6" Madrone, now dead, N.66°W., 31.1 ft.
20" now 22" D.Fir S.57°W., 32.5 ft., shows scribing
8" now 10" D.Fir S.18°E., 24.0 ft. shows scribing.

(Cont. Next Page)

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T31-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

16" now 18" D.Fir N.46½°W., 57.0 ft. shows scribing
6" now 8" D.Fir N.78°E., 38.0 ft. shows scribing.
Set Brass cap at cor. mkd: County Surveyors Office
R7W T 31 S R6W
S 25 | S 30
S 36 | S 31
1966

Survey by Howard Johnstone - For: Roseburg Lumber Co. - Feb.
1969 - M 33-49

Found new BTs.
Set 1" x 24" Iron pipe.

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - Aug. 27, 1996 - C.S. 65/9-1

Mon. Fd.- 2½" dia. Brass cap on a 1½" O.D. iron pipe,
protrudes 19" above ground.
1" I.D. Iron pipe protrudes 5" above ground. Fd.
along north edge of BC/IP.
Bt's Fd.- 6" madrone now root hole, bears N.20°E., 7.3'
1882 no other bt's from 1882 fd.
8" now 13" dia. D.Fir with a fully healed single
blaze, bears S.18°E., 24'. (agrees w/ rec.)
24" dia. 6' high D.Fir stump, with a fully healed
double blaze, bears S.57°W., 32.5' (agrees w/
rec.).
13" dia. D.Fir with a fully healed double blaze,
bears N.78°E., 38' (agrees w/ rec.).
18" dia. 6' high D.Fir stump with a fully healed
double blaze, bears N.46½°W., 57' (agrees w/
rec.).
New BT - 6" dia. Chinquapin double balzed and scribed
"T31S R6W S30 CS BT", bears N.25°E., 10'.