

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24 & 25, T31-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7945)

Set post cor. to secs. 19, 24, 25, and 30, on East slope of mountain, from which

- A Fir 24" dia., bears S.55°E., 57 lks. dist.
- Chinquapin 4" dia., bears N.54°E., 10 lks. dist.
- Laurel 4" dia., bears N.54°W., 19 lks. dist.
- Laurel 4" dia., bears S.71°W., 17 lks. dist.

W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7952-53)

Set a Chinquapin post, 4" sq., 4 ft. long, 24" in the ground, mkd. T31S R6W S19 on NE. face, S30 on SE. face, S25 on the SW. face, and R7W S24 on NW face; also two notches on the South and four notches on North angles of the same. The corner to secs. 19, 24, 25 and 30, from which

- A Laurel 6" dia., bears N.20°E., 15 lks. mkd. T31S R6W S19 BT.
- A Laurel 6" dia., bears S.65°E., 16 lks. dist. mkd. T31S R6W S30 BT.
- A Fir 6" dia., bears S.14°W., 8 lks. dist., mkd. T31S R7W S25 BT.
- A Laurel 12" dia., bears N.35°W., 21 lks. dist., mkd. T31S R7W S24 BT.

Old corner probably destroyed by fires.

Survey by Howard Johnstone, - For: Roseburg Lumber Co. - May 31, 1960 - M 18-66

Set section corner - 1½" x 24" Iron pipe.

- 6" D.Fir S.88°W., 32.8 ft.
- 14" D.Fir S.63°E., 35.0 ft.
- 30" D.Fir N.10°E., 55.1 ft.
- 7" S.Pine N.55°W., 23.9 ft.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - K.Cheney, P.L. Earle, crew - Jan. 3, 1977 - C.S. File 59/29-1

Found - 1¼" I.P. firmly set at sec. cor. as determined by Johnstone in 1962.

- 6" now 10" D.Fir bears S.88°W., 30.6 ft. (Rec. 32.9 ft.) Tree has well healed blaze. (single)
- 14" now dead, tipped out D.Fir, bears S.63°E., 35.0 ft. Tree has open double blaze scribed "T31S 6W S30 BT."

(Cont. Next Page)

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. cor. for 19 & 30; 24 & 25, T31-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

30" now 31" D.Fir bears N.10°E., 54.5 ft. (Rec. 55.1 ft.) Tree has partially healed single blaze.
7" now 9" S.Pine bears N.55°W., 23.3 ft. (Rec. 23.9 ft.) Tree has well healed double blaze.
I place 1" x 30" I.P. with brass cap attached at sec. cor. as determined by Johnstone, stamped: Douglas County Surveyor
T 31 S

R		R
7	<u>S 24 S19</u>	6
	<u>S 25 S 30</u>	
W		W

1977

New BT - A S.Pine 15" bears S.69°E., 53.3 ft. Tree double blazed and scribed "T31S R6W S30 CS BT"
All bearings and distances measured are to center of base of tree.