TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 for Sec. 18; and 13 of T31-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7944)

Set ¼ sec. post, from which
A Yew, 12" dia., bears N.49°E., 31 lks. dist.
Vine Maple, 6" dia., bears N.45°W., 11 lks. dist.

W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7954)

Set a Maple post, 40" long, 3" sq., 20" in the ground, mkd. ¼S on W. side for the ¼ sec. cor. from which
A Fir 14" dia., bears N.24°E., 37 lks. dist. mkd. ¼ S BT.
A Fir 28" dia., bears N.36°W., 52 lks. dist. mkd. ¼ S BT.
Old ¼ sec. cor. destroyed same and marks on witness trees.

BLM resurvey by James E. Jelley, under Group #'s 350 and 680, surveyed April/Sept. 1969 (DCSO records Vol. 35 Page 14494)

Point for the ¼ sec. cor. of secs. 13 & 18, at proportionate distance; there is no remaining evidence of the orig corner. Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

```
        ¼
   S 13|S 18
 R 7 W|R 6 W
    T 31 S
     1969
```

from which
A Fir 12" dia., S.22½°E., 84 lks. dist., mkd. ¼ S18 BT.
A Fir 24" dia., S.8½°W., 67½ lks. dist., mkd. ¼ S13 BT.

BLM resurvey by James L. White, under Group #1232, surveyed Dec. 1984/Jan. 1985 - (DCSO records Vol. 48 Page(s) 18183-84)

The ¼ sec.cor. on the W. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground with 1969 brass cap.
from which the remains of a bearing tree mkd. by Jelley
A root hole, bears S.8½°W., 67½ lks. dist., with down fir alongside, 26" dia., with healed blaze.
and new bearing trees
A Pine 5" dia., bears S.18°E., 96½ lks. dist. mkd. X BT.
A Fir 44" dia., bears S.25 3/4°W., 32 lks. dist. mkd. ¼ S13 BT on bark.

Fd. Ok by R Quimby - 10/2017 - C.S. File 65/99-12