

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T31-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7954-55)

-----  
Set a Cedar post, 4 ft. long, 4" sq., 22" in the ground, mkd. T31S R6W S7 on NE. face; S18 on SE. face; S13 on SW. face and R7W S12 on NW. face; also four notches on the South and two notches on the North angles of the same for the cor. to secs. 7, 12, 13 and 18, from which

- A Laurel 12" dia., bears N.76°E., 25 lks. dist., mkd. T31S R6W S7 BT.
- A Laurel 10" dia., bears S.25°E., 27 lks. dist., mkd. T31S R6W S18 BT.
- A Fir 24" dia., bears S.62°W., 11 lks. dist., mkd. T31S R7W S13 BT.
- A Laurel 8" dia., bears N.18°W., 29 lks. dist., mkd. T31S R7W S12 BT.

Old corner, 2.60 chs. North. Destroy same.

BLM resurvey by James E. Jelley, under Group #'s 350 and 680, surveyed April/Sept. 1969 (DCSO records Vol. 35 Page(s) 14495)

-----  
Point for the cor. of secs. 7, 12, 13 and 18, at proportionated distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 31 S  
R 7 W R 6 W  
S 12 S 7  
S 13 S 18  
1969

from which

- A Fir 7" dia., bears N.5°E., 68 lks. dist., mkd. T31S R6W S7 BT.
- A Fir 17" dia., bears S.12½°E., 148 lks. dist., mkd. T31S R6W S18 BT.
- A Fir 42" dia., bears S.32°W., 28 lks. dist., mkd. T31S R7W S13 BT.
- A Fir 8" dia., bears N.36½°W., 60½ lks. dist., mkd. T31S R7W S12 BT.