

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 100503

PRIMARY CORNER DESCRIPTION Angle Point Sec. 7; and 12, T31-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7943-44)

Set post cors. to secs. 7, 12, 13 and 18, from which
A Fir 36" dia., bears N.45°E., 16 lks. dist.
A Fir 36" dia., bears S.22°E., 12 lks. dist.
A Cedar 12" dia., bears N.27°W., 28 lks. dist.
A Laurel 8" dia., bears S.33°W., 53 lks. dist.

Douglas Co. Surveyors Office - John Powell and crew - June 1967 - C.S. File 54/31-46 See CS file for BLM opinion

Found - Hyde's section corner. No trace of NE or SW BT.
36" now 41" D.Fir S.22°E., 7.9 ft. Tree has been opened, scribe visible "BT". Ring count of these tree places it at the correct time to be Hyde's corner.

12" now 28" Cedar, N.27°W., 18.5 ft., center of tree burnt out.

Set Brass cap at cor. mkd: County Surveyors Office

	R	T 31	S	R
A.P.	7	S 12	S 7	6
		S 13	S 18	W
		1967		

New BTs -13" Cedar N.64½°W., 16.1 ft. mkd. T31S R7W S12 CS BT AP.

15" Cedar S.20°W., 29.8 ft. mkd. T31S R7W S13 CS BT AP.

24" D.Fir N.38°E., 23.4 ft. mkd. T31S R6W S7 CS BT AP.

A.P. corner Fd. and used in BLM resurvey by James E. Jelley, under Group #'s 350 and 680, surveyed April/Sept. 1969 (DCSO records Vol. 35 Page(s) 14495-96)