

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8006)

Set a Fir post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., mkd. ¼ S on N. face, from which
A Pine 30" dia., bears North 10 lks. dist. mkd. ¼ S BT.
A Pine 10" dia., bears S.50°E., 23 lks. dist. mkd. ¼ S BT

Survey by Howard Johnstone - For: Roseburg Lumber Company - May 31, 1960 - M 18-66

Set 3 x 3 Cedar post ¼ corner from remains of orig. BTs.
New BTs -7" D.Fir N.10°E., 8.3 ft.
7" D.Fir S.48°E., 28.5 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Cliff Stone, E. West - Oct. 1966 - C.S. File 54/31-36

Found - 3 x 3 post.
7" now 8" D.Fir N.10°E., 8.3 ft., shows scribing "¼S".
7" now 8" D.Fir S.48°E., 28.5 ft., shows scribing "¼S BT"

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 6 W

¼ $\frac{S \ 19}{S \ 30}$

1966

This corner lies on top of spur, approx. 600 ft. East of a logging road.