

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8009)

-----  
Set a Fir post 3 ft. long, 3" sq., 18" in the ground for the 1/4 sec. cor. mkd. 1/4 S on N. face, from which  
A Laurel 10" dia., bears N.5°E., 74 lks. dist. mkd. 1/4 S BT  
A Fir 60" dia., bears S.55°W., 33 lks. dist. mkd. 1/4 S BT.

Survey by Howard Johnstone - For: Roseburg Lumber Company - May 31, 1960 - M 18-66

-----  
Set 3 x 3 Cedar post 1/4 corner from original bearing trees.  
New BTs -I.Cedar S.14°E., 57.5 ft.  
D.Fir N.25°W., 68.0 ft.

Douglas Co. Surveyors Office - May 25, 1965 - C.S. 52/25-31

-----  
Found - Orig. 60" now 65" Fir S.55°W., 21.8 ft. shows "S" scribe (bark)  
24" I.Cedar S.14°E., 57.5 ft. shows "1/4S BT" on unhealed face.  
45" D.Fir N.25°W., 68.0 ft. shows "1/4SBT" on partially healed face.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 6 W

1/4 S 18  
S 19

1965

This corner lies on steep SE slope.

Cor. Fd. and used in BLM resurvey by James White, under Group #1232, surveyed Dec. 1984/Jan. 1985 (DCSO records, Vol. 48 Page 18180)

BLM Corrective Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, & Robert H Browning, Surveying Technician, under Group No. 2193, surveyed April/June 2008 - (DCSO records Vol. 56 Page(s) 22163)

-----  
The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 1/4" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd.

from which an original bearing tree

A fir, 55" dia., bears S.55°W., 21.8 ft., with a healed blaze.

and the remains of BTs mkd. by Johnstone, in 1960, reported by White

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed cedar stump, 28" dia., bears S.14°E., 57.4 ft.,  
with a healed blaze.  
A fir, 49" dia., bears N.25°W., 68.0 ft., with a healed  
blaze.