

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8015)

Set a Laurel post, 3 ft. long 3" sq., 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. face, from which
A Laurel 14" dia., bears N.51°W., 30 lks. dist. mkd. 1/4 S BT
A Laurel 12" dia., bears S.40°W., 27 lks. dist. mkd 1/4 S BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Cliff Stone, E. West, - Oct. 1966 - C.S. File 54/31-42

Found - Orig. 14" now 21" Laurel N.51°W., 19.8 ft. Tree had been partially opened, scribing found "BT"
No BT at S.40°W. 17.8 ft.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 6 W
1/4 S 6
S 7

New BTs -17" D.Fir S.27 1/2°W., 12.0 ft. mkd. 1/4 S7 CS BT.
17" D.Fir N.71°E., 4.4 ft. mkd. 1/4 S6 CS BT.

This corner lies in deep draw on top of small spur running N-S. Also about 150.0 ft East to draw & 200 ft West to draw.

BLM Corrective Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, & Robert H Browning, Surveying Technician, under Group No. 2193, surveyed April/June 2008 - (DCSO records Vol. 56 Page(s) 22167-8)

The 1/4 sec. cor. of secs. 6 & 7, perpetuated by the Douglas County Surveyor's Office in 1966, monumented with an iron post, 1 1/4" dia., firmly set, projecting 16 ins. above the ground, with brass cap (properly) mkd.

from which the remains of an original bearing trees
A madrone, 22" dia., bears N.51°W., 19.8 ft., with fragmentary scribe marks visible on an open blaze.
and the remains of BTs mkd. by the Douglas County Surveyor's Office

A sawed fir stump, 19" dia., bears N.78 3/4°E., 3.9 ft., with a healed blaze.

A sawed fir stump, 20" dia., bears S.26 1/4°W., 12.1 ft., with scribe marks BT visible on an open blaze.

and a new bearing tree

A fir, 5" dia., bears S.38 1/4°W., 11.7 ft., mkd. 1/4 S7 BT.
Each new bearing tree has a 2 1/2" x 1/4" magnetic nail (Mag Nail) driven at the base right side-center.

Corner is located on a spur, slopes N. 5° W.