

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & S. 31, T30-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7194)

-----  
Set quarter post, from which  
B.Oak 5" dia., bears S.45°E., 28 lks.  
B.Oak 5" dia., bears N.48°W., 77 lks.

BLM Dependent Resurvey by James Jelley, under Group #585 - Surveyed, July/Aug. 1965 (DCSO records, Vol. 33 Page 13814)

-----  
Point for the ¼ corner, at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd: T 30 S R 6 W  
¼ S 31  
S 6

from which  
A Pine 18" dia., bears N.36½°W., 150 lks., mkd. ¼ S31 BT.  
A Maple 18" dia., bears S.60°E., 430 lks., mkd. ¼ S6 BT.

Mark Smalley - For: Roseburg Resources - July, 1992 - M 112-52

-----  
Found - 26" Pine bears N.38½°W., 99.0 ft. healed face.  
24" maple bears S.62°E., 311.8 ft. found scribe (Rec. 283.8 ft.)  
Set 5/8" x 48" Iron rod and alum. cap on line between section corners at call distance from NW BT. (SE BT did not match record call distance.)  
New BTs -27" Fir bears N.20°W., 118.4 ft. scribed "¼ S31 BT".  
25" Fir bears S.73°E., 223.0 ft. scribed "¼ S6 BT".

DCSO-GIS Corner visitation - 4/7/2004 - Typed: 2/9/2011 - C.S. File 67/33-1

-----  
Monument - 5/8" rebar w/alum. cap  
Comment - OK

BLM resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2928 - surveyed July /Aug. 2018 - (DCSO records Vol. 59 Page(s) 23661-2)

-----  
The ¼ sec. cor. of secs. 6 and 31, reestablished by Smalley, in 1992, latitudinally on the line between the section cors. and longitudinally at 1965 Record from the NW BT mkd. by Jelley in 1965 and is accepted as a careful and faithful perpetuation of the cor. position as documented in a report by Herzberg dated August 8, 2018; monumented with an iron rod, 5/8" dia., 48" long, firmly set, projecting 11" (cont)

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & S. 31, T30-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

above ground, with an aluminum cap mkd. R.R. CO. T30S R7W 1/4 S31 S6 T31S 1992 LS 2354, from which the remains of bearing trees reported by Jelley

A maple, 26" dia., bears S.61 $\frac{3}{4}$ °E., 311.8 ft., with illegible scribe marks visible on decayed partially healed blaze. (Record, S.60°E., 283.8 ft.)

A hollow pine stump, 28" dia., bears N.38 $\frac{1}{4}$ °W., 99.0 ft., with illegible scribe marks visible on decayed blaze. (Record, N.36 $\frac{1}{2}$ °W.)

and the remains of the bearing trees mkd. by Smalley

A fir, 38" dia., bears S.77 $\frac{1}{2}$ °E., 222.7 ft., with a healed blaze.

A decayed fir stump, 34" dia., bears N.19°W., 117.7 ft., with a healed blaze.

At the corner point

Remove the iron rod from the area and set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 22" in the ground, with brass cap mkd.

T 30 S

R  $\frac{1}{4}$  S 31  
6 S 6

W

T 31 S

2018

from which a new bearing tree

A pine, 10" dia., bears N.76 $\frac{3}{4}$ °W., 32.6 ft., mkd.  $\frac{1}{4}$  S31 BT. Corner is located on level ground.