

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) )

-----  
Set a Fir post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which  
A Fir 7" dia., bears N.56°E., 5 lks. dist. mkd. ¼ S BT.  
A Fir 9" dia., bears N.88°W., 15 lks. dist. mkd. ¼ S BT.

Survey by Clifford M. Bryden - For: Roseburg Lumber Co. - Feb. 1960 - M 17-34

-----  
Set 3/4" x 18" Iron pipe at mid-distance between section corners. Scribed BTs:  
17" D.Fir N.27 3/4°E., 25.0 ft.  
15" D.Fir S.16½°W., 12.3 ft.

Gregg Neitsch - For: Carbon River Holdings LLC - 2/2023 - M181-76

-----  
Found - Disturbed 3/4" I.D. iron pipe per M17-34 in vicinity of proportion position for corner set monument at single proportion position & deposited found iron pipe horizontally alongside, from which bears.  
16" D.Fir snag with visible scribes, N.30°E., 25.5' (N.27¾°E., 25 0' M17-34).  
7" D.Fir scribed "XBT" this survey, N.73½°E., 9.0'.  
9" D.Fir scribed "XBT" this survey, S.14½°E., 5.8'.  
7" D.Fir scribed "XBT" this survey, S.62°W., 10.3'.  
8" D.Fir scribed "XBT" this survey, N.22½°W., 11.8'.  
Set - 5/8" rebar, 30" long, 24" in the ground with 2½" AC stamped per BLM manual of instructions & "PLS 77662"