

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8007)

-----  
Set a Fir post, 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which  
A Laurel 5" dia., bears N.50°E., 24 lks. dist. mkd. 1/4 S BT.  
A Fir 10" dia., bears S.70°W., 34 lks. dist. mkd. 1/4 S BT.

Survey by Howard Johnstone - For: Roseburg Lumber Company - May 31, 1960 - M 18-66

-----  
Found 3 x 3 Cedar post and original BT:  
18" D.Fir S.70°W., 22.4 ft.  
New BT - 8" D.Fir S.47°E., 14.6 ft.

Douglas Co. Surveyors Office - John Powell, Frank Jones, Cliff Stone, E. West - Oct.1966 - C.S. File 54/31-34

-----  
Found - 3 x 3 post.  
Orig. 10" now 20" D.Fir S.70°W., 22.4 ft., shows scribing "S".  
8" now 10" D.Fir S.47°E., 14.6 ft. shows scribing "1/4S".

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 6 W  
1/4 S 19 | S 20  
1966

This corner lies approx. 170 ft. East of a logging road.

Mark Smalley - For: Roseburg Resources - 12/2000 - M 132-60

-----  
Found - 1966 county brass cap on iron pipe.  
30" Fir, S.70°W., 22.4 ft. healed. Orig.  
Scribed- 12" Fir, N.47°W., 9.6 ft. "1/4 S BT"  
16" Fir, N.12°W., 24.9 ft. "1/4 S BT"  
7" I.Cedar, N.79°E., 35.8 ft. "1/4 S BT"