

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19, 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8007)

-
- Set a Fir post, 4 ft. long, 4" sq., 24" in the ground, for the cor. to secs. 17, 18, 19 and 20 mkd. T31S R6W S17 on NE.; S20 on SE.; S19 on SW.; and S18 on NW. faces, with 5 notches on E. and 3 notches on S. edges, from which
- A Fir 50" dia., bears N.55°E., 13 lks. dist. mkd. T31S R6W S17 BT.
 - A Fir 6" dia., bears S.53°E., 23 lks. dist. mkd. T31S R6W S20 BT.
 - A Laurel 20" dia., bears S.35°W., 59 lks. dist. mkd. T31S R6W S19 BT.
 - A Fir 6" dia., bears N.55°W., 19 lks. dist. mkd. T31S R6W S18 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Mike Darby, Jack Barnett - Oct. 1964 - C.S. File 52/25-26

-
- Found - Orig. 50" now 54" D.Fir N.55°E., 15.2 ft., recorded as 13 lks., shows old faint bark scribe "T31S R6W 7" and new "BT" in bark.
- Orig. 6" now 8" D.Fir S.47°E., 15.2 ft. (dead) recorded as S.53°E., shows good scars.
 - Orig. 20" now 20" Laurel S.35°W., 38.9 ft., down and dead, found "\\\" reverse scribe in rotted remains.
 - Orig. 6" now 9" D.Fir N.55°W., 12.5 ft., open and shows "BT"

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 6 W
S 18 S 17
S 19 S 20
1964

- New BTs -16" D.Fir S.79°E., 32.9 ft. mkd. T31S R6W S20 CS BT
- 17" D.Fir S.52°W., 35.4 ft. mkd. T31S R6W S19 CS BT
- 16" D.Fir N.22°E., 34.2 ft. mkd. T31S R6W S17 CS BT

BLM resurvey by James L. White, under Group #1232, surveyed Dec. 1984/Jan. 1985 (DCSO records Vol. 48 Page(s) 18178-79)

The Sec. cor., perpetuated and recorded by Tracy in 1964, monumented with an iron post, 1¼" dia., firmly set, projecting 4" above ground, with brass cap. from which the remains of original bearing trees:

- A Fir 57" dia., bears N.55°E., 23 lks. dist., no marks visible. (Rec. 13 lks.)

(Cont. Next Page)

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 10" dia., bears N.55°W., 19 lks. dist., with scribe marks BT visible on opened blaze.
and the remains of bearing trees mkd. by Tracy:
A Fir 18" dia., bears N.22°E., 49 lks. dist., with healed double blaze.
A Fir snag 13" dia., bears S.79°E., 50 lks. dist., with scribe marks T31S R6W S20 visible on partially healed double blaze.
A Fir 14" dia., bears S.55½°W., 54 lks. dist., with healed double blaze.
and new bearing trees:
A Fir 18" dia., bears N.81½°E., 60½ lks. dist., mkd. T31S R6W S17 BT.
A Western Red Cedar 10" dia., bears S.71½°E., 105 lks. dist., mkd. T31S R6W S20 BT.
A Fir 10" dia., bears S.13°W., 92 lks. dist. mkd. T31S R6W S19 BT.
A Western Red Cedar 6" dia., bears N.77½°W., 89 lks. dist. mkd. X BT.

Found OK by M. Smalley, Dec. 2000 - M132-60