

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8010)

Set a Fir post, 3 ft. long, 3" sq., 18" in the ground for ¼ sec.cor. mkd. ¼ S on W. face, from which

A Fir 6" dia., bears S.45°E., 11 lks. dist. mkd. ¼ S BT.

A Fir 8" dia., bears S.46°W., 22 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John Powell, Joe Brady, crew - Sept. 21, 1965 - C.S. File 52/25-32

Found - Orig. 6" now 12" D.Fir S.45°E., 11 lks., tree opened and BT scribe visible.

Orig. 8" now 12" D.Fir S.46°W., 22 lks., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 6 W

¼ S18 | S17

1965

New BT - 12" D.Fir S.45°E., 7.3 ft. scribed ¼ S17 CS BT.

BLM resurvey by James L. White, under Group #1232, surveyed Dec. 1984/Jan. 1985 - (DCSO records Vol. 48 Page(s) 18181)

The ¼ sec. cor., perpetuated and recorded by Powell in 1965, monumented with an iron post, 1¼" dia., firmly set, projecting 17" above ground, with brass cap.

from which the remains of the original bearing trees:

A Fir snag 16" dia., bears S.45°E., 11 lks. dist. with fragmentary scribe marks visible on partially healed double blaze.

A sawed Fir stump 14" dia., bears S.46°W., 22 lks. dist. with healed blaze.

and new bearing trees:

A Fir 21" dia., bears S.80½°E., 47 lks. dist. mkd. ¼ S17 BT.

A Fir 7" dia., bears N.81¼°W., 22 lks. dist. mkd. ¼ S18 BT.