

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8010)

 Set a Yew post, 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 7, 8, 17 and 18, mkd. T31SR6W S8 on NE.; S17 on SE.; S18 on SW.; and S7 on NW. faces, with 5 notches on E. and 4 notches on S. edges, from which
 A Fir 24" dia., bears N.42°E., 50 lks. mkd. T31S R6W S8 BT
 A Fir 20" dia. bears S.50°E., 45 lks. mkd. T31S R6W S17 BT
 A Yew 12" dia., bears S.1°W., 74 lks. mkd. T31SR6W S18 BT
 A Fir 40" dia., bears N.45°W., 5 lks. mkd. T31S R6W S7 BT

Douglas Co. Surveyors Office - John Powell, Joe Brady, crew -Sept. 1965 - C.S. File 52/25-33

 Found - Orig. 40" D.Fir now 59", N.45°W., 5 lks., shows bark scribe. Good tree.
 Orig. 24" D.Fir, now snag, N.42°E., 50 lks., shows bark scribe.
 Orig. 12" Yew, now 18", S.1°W., 74 lks. scribe visible. Good tree.
 Orig. 20" D.Fir, now burned snag, S.50°E., 45 lks.
 Set Brass cap at cor. mkd: County Surveyors Office

T	31	S	R	6	W	
		S	7		S	8
		S	18		S	17
						1965

 New BTs -59" D.Fir N.45°W., 4.6 ft. scribed T31S R6W S7 BT.
 36" D.Fir N.31°E., 68.0 ft. scribed T31S R6W S8 BT.
 49" D.Fir S.21°E., 77.5 ft. scribed T31S R6W S17 BT

BLM resurvey by Wayne L. Rogers, under Group #1293, surveyed Oct. 1985/March 1986 -(DCSO records Vol. 48 Page(s) 18231-2)

 The Sec. Cor., perpetuated and recorded by Powell in 1965, monumented with an iron post, 1¼" dia., firmly set, projecting 15" above ground, with brass cap, from which the remains of an original bearing tree
 A sawed Fir stump 48" dia., bears N.45°W., 5 lks. dist. with fragmentary scribe marks visible on burned blaze. and the remains of bearing trees mkd. by Powell
 A root hole bears N.31°E., 103 lks. dist. with a down Fir lying down hill, 36" dia., with fragmentary scribe marks visible on partially healed blaze.
 A sawed Fir stump 50" dia., bears S.21°E., 114 lks. dist., with fragmentary scribe marks visible on partially healed double blaze. continued next page

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and new bearing trees
A double Yew 14" dia., bears N.36°E., 119 lks. dist. mkd.
T31S R6W S8 BT.
A Fir 4" dia., bears S.20°E., 32 lks. dist. mkd. X BT.
A Fir 4" dia., bears S.41 3/4°W., 50 lks. dist. mkd. X BT.
Corner is located 1.10 chs. dist., East of Council Creek, 5
lks. wide, course N.20°E.

Jerry Estabrook - Bruce Webster - Oct. 19, 2003 - C.S. File
65/48-26

Condition report only

Found - 2½" brass cap on 1" galv. iron pipe 15" above grade.
A 48" dia. sawed fir stump with no bark, bears
N.45°W., 4.9 ft to center of stump with healed
face and tag. Now covered with automobile hood
wired on.
(A root hole bears N.31°E. 103 lks) now
indeterminate. With a down fir lying down hill
36" dia. with partially visible scribe and tag.
A tin covered sawed fir stump 50" dia. bears S.21°E.
75.2 ft with partially visible mostly healed
double blaze and tag.
A double Yew 17" measured below fork, bears N.36°E.,
79.3 (78.5) ft with visible scribe "T31 S R6W S8
BT" & tags front & back.
A fir 10" dia., bears S.20°E., 21.3 (21.1) ft with
healed double face and tag.
A fir 10" dia., bears S.41¾°W., 33.2 (33.0) ft with
healed double face. I place new tag.

Note - Distances to found bearing trees were measured with
EDM at approximate side center. Trees were red
band and face painted.
Dec. 19°E

Mark Heimburger - Crew: Bartt Heichel & Anthony Welch -
1/2018 - C.S. File 65/101-41

Found - 2½" brass cap on 1" iron pipe (properly mkd) from
which a:
48" dia. D.Fir stump with healed face, tag & auto
hood cover bears N.45°W., 4.9'
50" D.Fir stump with partially healed double blaze
& tin cover bears S.21°E., 75.2'
17" (now 18") double Yew with visible scribing "T31S
R6W S8 BT" bears N.36°E., 78.5'
10" (now 16") D.Fir with healed double face bears
S.20°E., 21.3' continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec Cor for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

10" (now 13") D.Fir with healed double face bears
N.42°W., 33.2'
Note - Oregon coordinate reference system, Cottage Grove -
Canyonville zone, NAD 88-(2011) EPOCH 2010
Per GIS Observation holding NGS CORS STATIONS
"RSBG" & "DDSN"
Lat. N.g42°53'00.8582" Lon. W.123°26'48.3756"
Compass Declination 15°