

PRIMARY CORNER DESCRIPTION 1/4 Cor. for SEcs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8013)

Set Laurel post 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor. mkd. 1/4 S on W. face, from which

A Laurel 12" dia., bears S.85°E., 70 lks. dist. mkd. 1/4 S BT.

A Laurel 30" dia., bears West, 50 lks. dist. mkd. 1/4 S BT.

BLM resurvey by Wayne L. Rogers, under Group #1293, surveyed Oct. 1985/March 1986 (DCSO records Vol. 48 Page(s) 18235)

Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an stainless steel post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked T 31 S R 6 W

1/4
S 7 | S 8
1985

from which

A Fir 10" dia., bears N.51°E., 5 1/2 lks. dist. mkd. 1/4 S8 BT

A Fir 20" dia., bears West, 41 lks. dist. mkd. 1/4 S7 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Jerry Estabrook - Bruce Webster - Oct. 19, 2003 - C.S. File 65/48-31

Found - A 3 1/4" BLM BC on 2 1/2" stainless pipe 6" above grade.

_____ A fir 10" dia., bears N.51°E., 3.6 ft with healed face & tag.

A fir 22" (20") dia., bears West, 27.1 ft with healed face & tag.

New - A fir 5" dia., bears S.23°W., 10.0 feet with "X" chop at eye level and a face scribed "BT" low to ground.

A fir 30" dia., bears S.58°E., 14.1 ft with face scribed "1/4 S8 BT".

Note - Distances to fd bearing trees were measured with EDM at approximate side center. New BTs were measured to a spike set at approx. side center. Trees were red band and face painted.

Dec. 19°E.