

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 and 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8013)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for the cor. to secs. 5, 6, 7 and 8, mkd. T31S R6W S5 on NE.; S8 on SE.; S7 on SW.; and S6 on NW. faces, with 5 notches on E. and S. edges, from which

A Laurel 8" dia., bears N.50°E., 29 lks. dist. mkd. T31S R6W S5 BT.

A Fir 26" dia., bears S.36°E., 37 lks. dist. mkd. T31S R6W S8 BT.

A Laurel 24" dia., bears S.16°W., 55 lks. dist. mkd. T31S R6W S7 BT.

A Laurel 20" dia., bears N.16°W., 37 lks. dist. mkd. T31S R6W S6 BT.

Douglas Co. Surveyors Office - James W. Bryon, Deputy - Mike Darby, Wm. Stoffel, crew - Sept. 16, 1963 - C.S. 52/25-16

-----  
Found - Orig. 8" now 10" rotted Laurel snag, N.50°E., 19.1 ft.

Orig. 26" now 40" Fir, S.36°E., 24.4 ft., shows scribing.

Orig. 20" now 25" Laurel N.16°W., 24.4 ft., shows scribing.

Stump hole that checks for SW bearing tree.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 6 W

S 6 | S 5

S 7 | S 8

1963

New BTs -Rescribe, now 25" Laurel N.16°W., 25.2 ft. "S6 CS BT".

8" R.Fir bears N.54°E., 43.5 ft. scribed S5 CS BT.

10" R.Fir bears S.14°W., 52.0 ft. scribed S7 T31S R6W CS BT.

Cor. Fd. and used in BLM resurvey by John M. Jelley, under Group #585, surveyed July/Aug. 1965 - (DCSO records, Vol. 33 Pages 13818/19)

BLM resurvey by Wayne L. Rogers, under Group #1293, surveyed Oct. 1985/March 1986 - (DCSO records Vol. 48 Page(s) 18235-36)

-----  
The Sec. cor., monumented with an iron post 1¼" dia., firmly set, projecting 10" above ground with 1963 brass cap,  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 and 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of the original bearing trees  
 A Fir 50" dia., bears S.36°E., 37 lks. dist. with fragmentary scribe marks visible on partially healed blaze.  
 A Madrone snag, 22" dia., bears N.16°W., 37 lks. dist. with fragmentary scribe marks visible.  
 and a bearing tree mkd. by Byron in 1963  
 A Fir 11" dia., bears S.13°W., 80 lks. dist. with healed double blaze. (Rec. 79 lks.)  
 and new bearing trees  
 A Fir 6" dia., bears N.77 3/4°E., 48 lks. dist. mkd. T31S R6W S5 BT.  
 A Pine 5" dia., bears N.34 1/4°W., 122 lks. dist. mkd. X BT.

From this point, U.S. Cost and Geodetic Survey triangulation station "SILVER BUTTE" 1942, bears S.51°47'E., 353.45 chs. dist., monumented with a standard brass tablet, 3 1/2" dia., cemented flush in bedrock, with top mkd. SILVER BUTTE 1942 and a triangle.

Jerry Estabrook - Bruce Webster - Oct. 19, 2003 - C.S. File 65/48-30

-----  
 Found - 2 1/2" brass cap on 1" galv. iron pipe 10" above grade.  
 A fir 50" dia., bears S.36°E., 24.4 ft. Now a snag with rotten face.  
 A Madrone snag 22" dia, bears N.16°W., 24.4 ft. Now a rotten shell at ground height. A fir 6" dia., (bears N.77 3/4°E., 31.7 ft). Now a windfall with healed face & tag.  
 A pine 5" dia., (bears N.34 1/4°W., 80.5 ft). Now a windfall with healed face & tag  
 A unrecorded fir 25" dia., bears S.88°E., 20.7 ft with healed face. I place new tag.  
 Set - A D.Fir 12" dia., bears S.66°W., 11.4 ft face scribed "T31S R6W S7 BT" and tagged.  
 A D.Fir 12" dia., bears S.1°W., 58.0 feet face scribed "T31S R6W S7 BT" and tagged.  
 A Ponderosa pine 9" dia., bears N.10°W., 84.5 ft face scribed "T31S R6W S6 BT" and tagged.  
 Distances to fd bearing trees were measured with EDM at approximate side center. New BTs were measured to a spike set at approx. side center. Trees were red band and face painted. FD. windfalls were not checked for bearing or dist.  
 Dec. 19°E.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Corrective Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, & Robert H Browning, Surveying Technician, under Group No. 2193, surveyed April/June 2008 - (DCSO records Vol. 56 Page(s) 22165-6)

-----  
The cor. of secs. 5, 6, 7, & 8, perpetuated by Estabrook, in 2003, monumented with an iron post, 1¼" dia. firmly set, projecting 12" above the ground, w/brass cap (properly) mkd from which the remains of an original bearing tree

A fir snag, 46" dia., bears S.36°E., 24.4 ft., with a healed blaze.

and the remains of a BT mkd. by Byron, in 1963, reported by Rogers

A fir, 12" dia., bears S.13°W., 52.8 ft., with a healed double blaze.

and the remains of a bearing tree mkd. by Rogers

A fir snag, 8" dia., bears N.77¾°E., 33.3 ft., with a healed blaze. (Record, 31.7 ft.)

and bearing trees mkd. by Estabrook

A fir, 13" dia., bears S.2½°E., 57.7 ft., with fragmentary scribe marks visible on a partially healed blaze.

A fir, 14" dia., bears S.62¾°W., 10.7 ft., with fragmentary scribe marks visible on a partially healed blaze.

A pine, 9" dia., bears N.31¾°W., 84.3 ft., with fragmentary scribe marks visible on a partially healed blaze.

and a BT mkd. by person(s) unknown, reported by Estabrook

A fir, 27" dia., bears East, 21.0 ft., with a healed blaze

and a new bearing tree

A pine, 12" dia., bears N.36¾°W., 83.5 ft., mkd. T31S R6W S6 BT.

The corner of sections 5, 6, 7, and 8.

Latitude: 42°53'54.18" N Longitude: 123°26'47.95"W.

Each new bearing tree has a 2½ inch x¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.