

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8016)

Set a Fir post 3 ft. long 3" sq., 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which
A Laurel 6" dia., bears East 16 lks. mkd. 1/4 S BT.
A Laurel 14" dia., bears N.89°W., 44 lks. mkd. 1/4 S BT.

BLM resurvey by John M. Jelley, under Group #585, surveyed July/Aug. 1965 - (DCSO records Vol. 33 Page(s) 13820)

Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2" dia., 22" in the ground, with brass cap marked T 31 S R 6 W

1/4
S 6 S 5
1965

from which

A Fir 10" dia., bears N.59°E., 60 lks. mkd. 1/4 S5 BT.
A Fir 15" dia., bears N.71°W., 29 1/2 lks. mkd. 1/4 S6 BT

BLM Rehabilitation by Timothy J. Moore, Cadastral Surveyor, under Group #1000, surveyed Oct. 26, 2000. (DCSO rec. Vol. 53 page(s) 20597)

The 1/4 sec. cor. of secs. 5 & 6, monumented with an iron post, 2 1/2 ins. dia., firmly set, projecting 6" above ground, with brass cap mkd. T 31 S R 6 W

1/4
S 6 | S 5
1965

from which the remaining bearing tree mkd. by Jelley

A fir, 20" dia., bears N.59°E., 19.6 ft., with a healed blaze. (Record, 39.6 ft.)

and a new bearing tree

A fir, 7" dia., bears N.50°W., 33.1 ft., mkd. 1/4 S6 BT.

Corner is located on the Jelley blaze line, and 50 ft. N. and 60 ft. E. of a graveled road, 25 ft. wide, which bears N. 50° W. and S. 50° E.

The new bearing tree has a 2 1/2" x 1/4" magnetic nail (MAG-NAIL) driven at the base on the right side-center.