

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32 T30-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Under Contract #56, dated March 1855 (DCSO records Volume 17 Page 7194)

-----  
Set post, cor. to secs. 31, 32, 5 & 6, from which  
A Laurel 8" dia., bears N.86°E., 19 lks.  
A Laurel 6" dia., bears N.3°W., 40 lks.  
A Laurel 5" dia., bears S.38°E., 25 lks.  
A Red Fir 25" dia., bears S.85°W., 30 lks.

Cor. Fd. and used in GLO survey by W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Pg. 8016)

BLM dependent resurvey by James Jelley, under Group #585 - Surveyed July/Aug. 1965 (DCSO records, Vol. 33 Page 13813)

-----  
Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd:  
T 30 S R 6 W  
S 31 S 32  
S 6 S 5  
T 31 S  
1965

from which  
An Oak 10" dia., bears N.73°E., 36 lks. dist., mkd. T30S R6W S32 BT.  
A Fir 8" dia., bears S.62°E., 26 lks. dist., mkd. T31S R6W S5 BT.  
A Fir 18" dia., bears S.16°W., 28 lks. dist., mkd. T31S R6W S6 BT.  
A Fir 15" dia., bears N.3½°W., 26 lks. dist., mkd. T30S R6W S31 BT.  
The corner is located on a ravine, drains N.65°W.

Fd. OK, July 1992, Mark Smalley, M 112-52