

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; & 5 of T32-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7949)

Set post on North slope of Mt., from which
A Fir 16" dia., bears N.11°E., 42 lks. dist.
A Fir 5" dia., bears S.42°W., 35 lks. dist.

Douglas Co. Surveyors Office - John Powell, Frank Jones, C. Stone, crew - Nov. 1966 - C.S. File 54/31-41

Found - 16" now 21" Fir N.11°E., 27.7 ft. Tree had been opened, scribe visible "B". Broken top.
5" now 7" Fir S.42°W., 23.1 ft. scribe visible "¼S"
Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 6 W
¼ S 32
S 5
T 32 S R 6 W
1966

New BTs -22" D.Fir N.19°E., 38.0 ft. mkd. ¼ S32 CS BT.
17" D.Fir S.27°W., 41.3 ft. mkd. ¼ S5 CS BT.

Gregg Neitsch - For: Carbon River Holdings LLC - 2/2023 - M181-76

Found - 1" I.D. GIP with 2½" BC stamped "T31S R6W ¼S S32 S5 T32S COUNTY SURVEYORS OFFICE 1966", 12" above ground, from which bears:
21" D.Fir stump, 7' high, with visible scribes N.12¾°E., 28.7' (N.11°E., 27.7' 1966).
17" D.Fir stump, 7' high, with healed blaze N.19°E., 37.4' (N.19°E., 38.0' 1966).
27" D.Fir with healed blaze S.27°W., 39.9' (S.27°W., 41.3' 1966).
New - 10" D.Fir scribed "XBT" this survey, S.15¾°E., 31.4'