

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8005)

Set a Cedar post 4 x 5 (sawed) 4 ft. long, 20" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
An Alder 10" dia., bears N.65°E., 17 lks. dist. mkd. ¼ SBT
A Fir 48" dia., bears S.20°W., 29 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John Powell, Frank Jones, Cliff Stone, crew - Oct. 1966 - C.S. File 54/31-33

Found - 10" now 18" Alder N.65°E., 11.2 ft., shows good scar.
48" now 38" D.Fir S.20°W., 19.1 ft., bark scribe.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 6 W

¼ $\frac{S\ 20}{S\ 29}$
1966

Remarked - 38" D.Fir S.20°W., 19.1 ft. "¼ S29 CS BT"
New BTs - 15" W.Fir N.1½°W., 34.8 ft. mkd. "¼ S20 CS BT"
12" Hemlock S.14½°E., 31.7 ft. scribed ¼ S29 CSBT
This corner lies approx. 100 ft. West of logging road.

Douglas Co. Surveyors Office - R. Smith, S. Flause, Aug. 20. 1996 - C.S. 65/9-4

Found - 2½" Brass cap on a 1½" O.D. iron pipe, protrudes 25" above ground.

Orig. 10" Alder, bearing N.65°E., 11.2 ft. now gone.
48" now 48" dia. 1½ ft. high D.Fir stump, no bark scribing visible, a healed lower blaze is visible, bears S.20°W., 19.1 ft. (agrees with record.) O.B.T.

Both BT's marked by DCSO in 1966 are now gone.

New - Position of BC/IP is referenced, monument is set deeper, now protrudes 7" above ground. BC/IP is 36" long.

6" dia. D.Fir, double blazed and scribed "¼ S20 CS BT" bears N.51½°W., 36.6 ft.

4" dia. D.Fir, double blazed and scribed "X BT" bears S.64½°E., 23.2 ft.

9" dia. G.Fir, double blazed and scribed "¼ S20 CS BT" bears N.41°E., 46.2 ft.

12" dia. G.Fir, double blazed and scribed "¼ S29 CS BT" bears S.12°W., 61.9 ft.

Found OK by M. Smalley, Dec. 2000 - M132-60