

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8008)

Set a Laurel post, 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec.cor. mkd. 1/4 S on N. face, from which
A Pine 40" dia., bears S.45°E., 68 lks. dist. mkd. 1/4 S BT
A Pine 12" dia., bears N.80°W., 88 lks. dist. mkd. 1/4 S BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Mike Darby, Jack Barnett - Oct. 1964 - C.S. File 52/25-28

Found - Orig. 12" now 28" Pine N.80°W., 58.1 ft., open and shows "1/4S BT"
Orig. 40" now 40" Pine snag S.40°E., 44.9 ft. recorded S.45°E. Did not open.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 6 W
1/4 S 17
S 20
1964

New BTs -6" D.Fir S.9°E., 7.8 ft. mkd. 1/4 S20 CS BT.
6" D.Fir N.6°W., 23.4 ft. mkd. 1/4 S17 CS BT.

Mark Smalley - For: Roseburg Resources - 12/2000 - M 132-60

Found - 1964 County brass cap on iron pipe.
13" Fir, N.6°W., 23.4 ft. healed.
11" Fir, S.9°E., 7.8 ft. healed.
28" Pine, N.80°W., 58.1 ft. scribe visible. Orig.
Scribed- 8" Fir, N.52°W., 20.7 ft. "1/4 S BT"