

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8014)

-----

Set Laurel post 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on N. Face, from which

A Laurel 26" dia., bears North, 54 lks. dist. mkd. 1/4 S BT

A Laurel 7" dia., bears S.28°E., 26 lks. dist. mkd. 1/4 S BT

BLM resurvey by John M. Jelley, under Group #585, surveyed July/Aug. 1965 - (DCSO records Vol. 33 Page(s) 13818)

-----

The 1/4 sec. cor., monumented with a wooden stake, 3" square, firmly set, extending 36" above ground, from which the original bearing trees:

The rotted remains of a Madrone stump, 38" dia., bears North, 47 lks. dist., slope dist., 54 lks., no marks remaining. (Rec. 54 lks.)

A Madrone 14" dia., bears S.28°E., 26 lks. dist., with old opened blaze, no marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 23 ins. in the ground, with brass cap marked T 31 S R 6 W

1/4 S 5  
S 8  
1965

from which new bearing trees

A Fir 22" dia., bears N.39°W., 51 lks. dist. mkd. 1/4 S5 BT.

A Fir 12" dia., bears S.49 1/2°W., 37 lks. dist. mkd. 1/4 S8 BT

Jerry Estabrook - Bruce Webster - Oct. 19, 2003 - C.S. File 65/48-28

-----

Found - 3 1/4" BLM brass cap on 2 1/2" iron pipe 6" above grade. A fir 24" (22") dia., bears N.39°W., 33.7 ft with healed face. Now a stump, I place new tag.

A fir 12" dia., bears S.49 1/2°W, 23.7 (24.4) ft with healed face and tag.

New - A D.Fir 9" dia., bears N.79°E., 30.7 ft to a spike placed at approx. side center marked "1/4 S5 BT".

A D.Fir 43" diameter, bears S.62°E., 39.3 ft to a spike placed at approx. side center mkd "1/4 BT"

Note - Distances to fd bearing trees were measured with EDM at approximate side center. Trees were red band and face painted.

Dec. 19°E

Fd. ok by Kris DeGroot - 7/2007 - M153-68