

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7991)

-----  
Set a Laurel post, 3 ft. long, 3" sq., 18" in the ground for 1/4 sec.cor. mkd. 1/4 S on W. face, from which  
A Fir 22" dia., bears N.70°E., 23 lks. dist., mkd. 1/4 S BT.  
A Fir 40" dia., bears S.41°W., 23 lks. dist., mkd. 1/4 S BT.

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Cliff Stone, crew - Oct. 1966 - C.S. File 54/31-23

-----  
Found - 22" D.Fir now 40", N.70°E., 15.2 ft., bark scribe, faint "1/4 BT"  
40" D.Fir now 47", S.41°E., 15.2 ft. bark scribe, faint "1/4S" (Field notes checked - this is not a typo error)

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 6 W  
1/4 S32 | S33  
1966

New BTs -40" Cedar S.73°W., 30.8 ft. mkd. 1/4 S32 CS BT.  
16" Laurel S.32°E., 6.7 ft. mkd. 1/4 S33 CS BT.