TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7993)

Set a Fir post, 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 14" dia., bears East, 8 lks. dist. mkd. ¼ S BT.
A Fir 10" dia, bears N.80°W., 5 lks. dist. mkd. ¼ S BT.

Survey by R.H. Gee - For: R.J. Henrickson and F.McCornack - Dec. 29-30, 1954 - C.S. File 41/338-2

Found - BT to Sec. 28 present. Scars very plain.
Reset corner with 3/4" Iron pipe using recorded distance and bearing. BTs are as follows:
Fir 18", East 5.3 ft. (orig. BT)
Incense Cedar 12", S.60°30'W., 8.8 ft. scribed ¼ S29 T31S R6W WM. This is new BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Cliff Stone, crew - Oct. 1966 - C.S. File 54/31

Found - 3/4" Iron pipe at ¼ corner.
Orig. 18" now stump, East 5.2 ft.
12" I.Cedar now 14" S.60½°W., 8.8 ft. scribe visible
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 6 W
¼ S29|S28
1966
New BT - 13" I.Cedar N.87°E., 28.2 ft. mkd. ¼ S28 CS BT.

Mark Smalley - for:Kenneth & Hallie Ford - Jan 1995 - M121-57

Mon. Fd. - 1966 Co. Brass cap & Iron pipe
Bt's Fd. - 16" cedar, N.87°E. 28.2' healed
18" cedar, S.60½°W. 8.8' healed
18" fir, East 5.3' stump original
New BT's - 16" cedar, N.60°E. 12' "¼ S BT"
7" fir, N.1°E 34.2' "¼ S BT"