TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7994)

A Cedar, 10" dia., which I marked ¼ S on W. face, for ¼ sec. cor., from which
An Alder 14" dia., bears N.78°E., 40 lks. dist. mkd. ¼ S BT.
A Cedar 6" dia., bears S.65°W., 13 lks. dist. mkd. ¼ S BT.

Survey by Clifford M. Brydon - For: Roseburg Lumber Co. - Feb. 14, 1957 - C.S. File 42/250-2

Found - Old BT, Cedar 18", S.62½°W., 7.3 ft.
Set 2" x 4" x 4 ft. cedar post at corner point, from which
New BT, a Fir 18", N.81°E., 79.0 ft. scribed R.E. 3937 BT.

Douglas Co. Surveyors Office - Vernon Tracy, Mike Darby, Jack Barnett - March 5, 1965 - C.S. File 52/25-30

Found - Squared post as recorded by Brydon.
Orig. 6" now 19" Cedar S.65°W., 8.6 ft., open and found "¼" scribe.
No trace of other orig. BT, nor BT recorded by Brydon.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 6 W
¼ S 20 | S 21
1965
New BTs -19" D.Fir N.55°E., 72.0 ft. mkd. ¼ S21 CS BT.
22" Cedar N.66°W., 21.6 ft. mkd. ¼ S20 CS BT.
This corner lies approx. 60 ft. South of spring branch flowing N.W.

Mark Smalley - For: Roseburg Resources - 12/2000 - M 132-60

Found - 1965 county brass cap on iron pipe.
20" Cedar, S.63°W., (S.65°W.) 8.6' scribe vis. orig.
44" Fir, N.55°E., 72.0 ft. windfall
23" Cedar N.66°W., 21.6 ft. healed.
24" Fir, N.81°E., 79.0 ft. healed.
Scribed- 9" Fir, N.28°E., 42.2 ft. "¼ S BT"