

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7995)

Set a Fir post, 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 16, 17, 20 and 21, mkd. T31S R6W S16 on NE.; S21 on SE.; S20 on SW.; and S17 on NW. faces, with 4 notches on E. and 3 notches on S. edges, from which
A Laurel 14" dia., bears N.50°E., 46 lks. dist. mkd. T31S R6W S16 BT.
A Laurel 10" dia., bears S.51°E., 64 lks. dist. mkd. T31S R6W S21 BT.
A Laurel 20" dia., bears S.40°W., 103 lks. dist. mkd. T31S R6W S20 BT.
A Laurel 18" dia., bears N.60°W., 105 lks. dist. mkd. T31S R6W S17 BT.

Douglas Co. Surveyors Office - Milo Godfrey, Deputy - Wm. Stoffel, Mike Stone, Mike Darby, crew - June 1964 - C.S. File 52/25-17

Found - 14" now 17" Laurel N.50°E., 30.4 ft. scribing visible "31-6-16".
10" now 12" Laurel S.51°E., 42.2 ft., badly burnt.
20" now 29" Laurel S.40°W., 68.0 ft. "BT" visible, badly burnt.
18" now 27" Laurel N.60°W., 69.3 ft., scribing visible "31S R6W S17".
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 6 W
17 | 16
20 | 21
1964
New BTs -5" Fir S.46°E., 36.3 ft. mkd. S21 CS BT.
5" Fir S.10°W., 15.0 ft. mkd. S20 CS BT.

Fd. OK, Bruce Shaner, June 3, 1980, RM 3-32

Douglas Co. Surveyor's Office, Randall Smith, Stephen Flause, Aug. 8, 1994 - C.S. File 64/52-14

Found - 2½" brass cap on a 1½" O.D. iron pipe, protrudes 9" above ground and leaning 16" south of plumb.
Accessories Found -
-14" now 20" dia. Madrone with a partially healed single blaze, scribe marks visible "3 6 6" bears N.50°E., 27.3 ft. (rec. N.50°E., 30.4 ft. possible slope measurement) O.B.T.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Corner to Sections 16, 17, 20 & 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Accessories Found cont. -
-20" now 29" dia. 3 ft. high rotted Madrone stump with evidence of a blaze, no scribing visible, bears S.40°W., 72.4 ft. (rec. S.40°W., 68.0 ft.) O.B.T.
-18" now 27" dia. 3 ft. high rotted Madrone stump with evidence of a blaze and scribing visible. bears N.57½°W., 65.8 ft. (rec. N.60°W., 69.3 ft.) O.B.T.
-original SE BT not found.
-5" now 12" dia. D.Fir with a fully healed single blaze, bears S.46°E., 36.3 ft. (agrees with rec.) 1967
-5" now 12" dia. D.Fir with a fully healed single blaze, bears S.10°W., 15.0 ft. (agrees with rec.) 1967
Monument Set - returned BC/IP to plumb position, protrudes 8" above ground.
New Accessories -
-14" dia. D.Fir double blazed and scribed "T31S R6W S17 CS BT" bears N.80°W., 36.4 ft.

Mark Smalley - For: Roseburg Resources - 12/2000 - M 132-60

Found - 1964 county brass cap on iron pipe
14" Fir, S.10°W., 15.0 ft., healed.
13" Fir, S.46°E., 36.3 ft., healed.
16" Laurel, N.50°E., 30.4 ft. axe work. Orig.
14" Fir, N.80°W., 36.4 ft., scribe visible, no rec.
25" Laurel stump, N.60°W., 69.3 ft. Orig.
Remains of Laurel stump S.51°E., 42.2 ft. Orig.
Scribed- 7" Fir, S.73°E., 17.8 ft. "S 21 BT"

BLM Corrective Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, & Robert H Browning, Surveying Technician, under Group No. 2193, surveyed April/June 2008 - (DCSO records Vol. 56 Page(s) 22161)

The cor. of secs. 16, 17, 20, & 21, perpetuated by Godfrey, in 1964, subsequently perpetuated by the Douglas County Surveyor's Office in 1994, further perpetuated by Mark F. Smalley, in 2000, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees
A madrone, 16" dia., bears N.50°E., 27.3 ft., with a healed blaze. (Record, 30.4 ft.)
A sawed madrone stump, 17" dia., bears S.51°E., 42.3 ft., with no marks visible.
A sawed madrone stump, 27" dia., bears N.60°W., 65.9 ft., with a healed blaze. (Record, 69.3 ft.)

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec Cor for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Godfrey
A fir, 15" dia., bears S.45 $\frac{3}{4}$ ° E., 36.1 ft., with a healed blaze.
A fir, 15" dia., bears S.10 $\frac{1}{4}$ °W., 15.0 ft., with a healed double blaze.
and bearing tree mkd. by the Douglas County Surveyor's Office
A fir, 15" dia., bears N.80°W., 36.1 ft., with a healed double blaze.
and bearing tree mkd. by Smalley
A fir, 9" dia., bears S.73 $\frac{3}{4}$ °E., 17.7 ft., with a healed blaze.
The geographic position (NAD 1983 (CORS 96)) of the following corners, as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, using for control National Spatial Reference System Continuously Operating Reference Stations (CORS) CAPE BLANCO CORS ARP (CABL), and National Cooperative CORS Network Station ROSEBURG COOP CORS ARP (DCSO), is as follows:
The corner of sections 16, 17, 20, and 21.
Latitude: 42°52'10.13"N. Longitude: 123°25'37.48"W.