

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7996)

Set Fir post 3 ft. long, 3" sq., 18" in ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 26" dia., bears N.72°W., 24 lks. dist. mkd. ¼ S BT.
A Fir 8" dia., bears S.72°E., 31 lks. dist. mkd. ¼ S BT.

Survey by Bruce A. Shaner, L.S. #430 - For: C & D Lumber Co. June 1980 - RM 3-32

Set Brass cap mkd. T31S R6W W.M. ¼ S S17 S16 RLS 430 1980.
BTs - 6" D.Fir scribed ¼ S S16 BT, bears S.78°E., 10.9 ft.
6" D.Fir scribed ¼ S S17 BT, bears N.88°W., 16.2 ft.
The brass cap falls snugly up against a 6" D.Fir stump.

BLM Corrective Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, & Robert H Browning, Surveying Technician, under Group No. 2193, surveyed April/June 2008 - (DCSO records Vol. 56 Page(s) 22162)

The ¼ sec. cor. of secs. 16 and 17, reestablished by Bruce A. Shaner, and is accepted as the cor., monumented with an iron post, 2½" dia., projecting 10" above the ground, with brass cap (properly) mkd.
from which bearing trees mkd. by Shaner
A fir, 12" dia., bears S.78¾°E., 10.8 ft., with a healed blaze.
A fir, 12" dia., bears N.81¾°W., 16.1 ft., with a healed blaze.