

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7998)

A Cedar 24" dia., which I marked $\frac{1}{4}$ S on W. face, for $\frac{1}{4}$ sec. cor., from which

A Fir 30" dia., bears N.80°E., 10 lks. dist. mkd. $\frac{1}{4}$ S BT.

A Fir 8" dia., bears S.70°W., 9 lks. dist. mkd. $\frac{1}{4}$ S BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17305-06)

Point for the $\frac{1}{4}$ sec. cor., at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 31 S R 6 W
 $\frac{1}{4}$
S 8 | S 9
1980

from which

A Fir 9" dia., bears S.31°E., 11 lks. dist. mkd. $\frac{1}{4}$ S9 BT.

A Fir 5" dia., bears N.71°W., 32 lks. dist. mkd. $\frac{1}{4}$ S8 BT.

Mark Heimburger - Crew: Bartt Heichel & Anthony Welch - 1/2018 - C.S. File 65/101-40

Found - 2 1/2" BLM brass cap on a 2 1/2" iron pipe from which a:
9" (now 15") fir w/healed face bears S.31°E., 7.3'

5" (now 10") fir w/healed face bears N.71°W., 21.1'

New BTs- 7" fir scribed "X BT" in double face bears N.5°W. 5.9'

6" fir scribed "X BT" in double face bears S.71°E. 24.4'

Note - Oregon coordinate reference system, Cottage Grove - Canyonville zone, NAD 88-(2011) EPOCH 2010

Per GIS Observation holding NGS CORS STATIONS "RSBG" & "DDSN"

Lat. N42°53'00.27.9335" Long. W123°25'36.5665"

Compass Declination 15°