

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7998-99)

A Fir tree, 72" dia., which I marked, T31S R6W S4 on NE.; S9 on SE.; S8 on SW.; and S5 on NW. faces, with 4 notches on E. and 5 notches on S. edges, for cor. to secs. 4, 5, 8 and 9, from which

- A Laurel 7" dia., bears N.35°E., 50 lks. dist. mkd. T31S R6W S4 BT.
- A Laurel 6" dia., bears S.45°E., 7 lks. dist. mkd. T31S R6W S9 BT.
- A Laurel 12" dia., bears S.58°W., 115 lks. dist. mkd. T31S R6W S8 BT.
- A Laurel 10" dia., bears N.68°W., 45 lks. dist. mkd. T31S R6W S5 BT.

BLM resurvey by John M. Jelley, under Group #585, surveyed July/Aug. 1965 (DCSO records Vol. 33 Page(s) 13816)

The Sec. corner, occupied by the rotted and burned remains of the original Fir corner tree, from which the original bearing trees:

- The rotted remains of a Madrone stump, size indeterminate bears N.35°E., 50 lks. dist.
- Rotted remains Madrone stump, S.45°E., 7 lks.
- A burned Madrone 33" dia., bears S.58°W., 107 lks. dist., no marks remaining. (Rec. 115 lks.)
- A Madrone 27" dia., bears N.68°W., 47 lks. dist., with old axe marks visible in reverse on burned overgrowth. (Rec. 45 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, in the center of the shell of the original corner tree, with brass cap marked T 31 S R 6 W

S 5	S 4
S 8	S 9
1965	

from which new bearing trees

- A Fir 17" dia., bears N.48°E., 62 lks. dist. mkd. T31S R6W S4 BT.
- A Fir 30" dia., bears S.74½°E., 75 lks. dist. mkd. T31S R6W S9 BT.
- A Fir 8" dia., bears S.66°W., 36 lks. dist. mkd. T31S R6W S8 BT.
- A Fir 23" dia., bears N.12°W., 46 lks. dist. mkd. T31S R6W S5 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Cor. Fd. and Used in BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17306)

Jerry Estabrook - Bruce Webster - Oct. 19, 2003 - C.S. File 65/48-27

- 
- Found - 3¼" BLM brass cap on 2½" iron pipe 6" above grade.  
A Madrone 24" (27") dia., bears N.68°W., 34.4 ft (31.02 ft & 29.70 ft). With tag & old axe marks  
A fir 18" (17") dia., bears N.62°E. (N.48°E.) 40.5 (40.9) ft. Now 4± ft tall stump still with bark with healed face.  
A fir 23" (30") dia., bears S.74½°E., 49.5 ft. Now 5± ft tall tin covered stump without bark with healed face and tag.  
A fir 35" (23") dia., bears N.12°W., 31.2 (30.4) ft, with healed face and tag.  
A fir 6" dia., bears S.8°E., 30.5 ft, face scribed "T31S R6W S8" "BT".  
A 5/8" iron rod with a yellow plastic cap "BTS", bears S.72°E., 20.1 ft.

Note - Distances to bearing trees were measured with EDM at approximate side center. Trees were red band and face painted.  
Dec. 19°E

Kris DeGroot - For: Silver Butte Timber Co. - Jan 2004 - M 137-77

- 
- Found - 2½" USBLM standard brass capped iron post by Jelly, USBLM in 1965, loosely set in rotted remains of the orig. corner tree (properly) stamped:  
From which orig. BTs by Byars in 1882:  
A 19" Madrone bears N.71°05'E., 33.9 ft. with axe marks visible (rec. N.68°W., 47 lks.)  
A 25" D.Fir high cut stump bears S.74°05'E., 49.4 ft. with healed blaze (rec. S.74½°E., 75 lks.)  
A 36" D.Fir bears N.10°10'W., 30.6 ft. with healed blaze (rec. N.12°W., 46 lks.)  
New - A 6" D.Fir bears S.7°10'E., 30.5 ft. scribed "T31S R6W S8 BT"  
A 5/8"x30" iron rod bears S.71°05'13"E., 20.00 ft.

Fd. ok by Kris DeGroot - 7/2007 - M153-68