

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 8000)

Set Oak post, 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which
A B.Oak 6" dia., bears S.52°E., 10 lks. dist. mkd. 1/4 S BT.
A Laurel 7" dia., bears S.72°W., 27 lks. dist. mkd. 1/4 S BT

Survey by R.H. Gee - For: R.J. Henrickson and F. McCornack - Dec.29-30, 1954 - C.S. File 41/338-4

Found - Laurel BT, scribe marks very plain. Tree has fallen over. Reset corner from stump hole using recorded dist. and bearing.
Corner is a 3/4" Iron pipe.
Marked 2 new BTs which are as follows:
Fir 14", N.33°W., 3.4 ft. scribed 1/4 S5 T31S R6W BT.
Fir 14", S.48°10'W., 6.8 ft scribed 1/4 S4 T31S R6W BT

BLM resurvey by John M. Jelley, under Group #585, surveyed July/Aug. 1965 (DCSO records Vol. 33 Page(s) 13817)

The 1/4 sec. cor., perpetuated and recorded by R.H. Gee, in 1954, from an original bearing tree which is no longer in existence, monumented with an iron pipe, 3/4" dia., firmly set, extending 4" above ground, from which bearing trees marked by Gee:

A Fir 16" dia., bears S.48°E., 10 lks. dist., with illegible scribe marks visible on partly healed double blaze.

A Fir 16" dia., bears N.33°W., 5 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 18 ins. in the ground, over local iron pipe, to bedrock, and in a mound of stone, 2 ft. base, to top, with brass cap marked

T 31 S R 6 W

1/4
S 5 | S 4
1965

Kris DeGroot - For: Silver Butte Timber Co. - Jan 2004 - M 137-77

Found - 2 1/2" USBLM standard brass capped iron post by Jelly, USBLM in 1965, firmly set projecting 6" above the ground, (properly) marked.

continued next page

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From which BTs by R.H. Gee in 1954:
A 17" D.Fir stump bears S.51°05'W., 7.0 ft. (Rec. S.49°10'W., 6.8 ft.)
A 14" D.Fir, 12 ft. tall snag, bears N.29°10'W., 3.6 ft. (Rec. N.33°W., 3.4 ft.)
New BTs- A 20" D.Fir bears S.34°40'E., 70.1 ft. scribed "¼ S4 BT"
A 14" D.Fir bears S.17°50'W., 31.0 ft. scribed "¼ S5 BT"
A 5/8" x 30" iron rod bears S.17°52'37"E., 20.00 ft.
A 5/8" x 30" iron rod bears S.71°28'12"W., 20.00 ft.

Fd. ok by Kris DeGroot - 7/2007 - M153-68