

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; and S. 4 of T32-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7948)

Set ¼ sec. post on N. slope of Mt. from which
A Fir 8" dia., bears N.60°E., 47 lks. dist.
A Fir 12" dia., bears S.55°W., 5 lks. dist.

Douglas Co. Surveyors Office - John Powell, Frank Jones, C. Stone, E. West, crew - Oct. 1966 - C.S. File 54/31-39

Found - 12" Fir, now down and rotten, S.55°W., 3.3 ft. Found old reverse scribe marks.
8" Fir now 11", N.60°E., 31.0 ft. shows very good face.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 6 W
S 33
S 4
T32S
1966

New BT - 26" D.Fir S.88°W., 49.4 ft. mkd. ¼ S4 CS BT.
PK nail in rock, West, 3.6 ft.

This corner lies on very steep, North slope, 2.5 ft. West of rocky point about 12 ft. high.

FD. OK, Feb. 1985, by O. Frederick, M 90-67 and C.S. File 63/11