

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION ¼ cor of sec. 28 & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

ORIG. GLO SURVEY - by William H. Byars - Contract #448 dated June 13, 1882

-----  
Set - Laurel post, 3' long, 3" sq., 18" in the ground, for ¼ cor. mkd. ¼ S on N. face.

BT's- 34" dia. Pine, bears S.47°W., 73 lks. mkd. ¼ S BT.

30" dia. Fir, bears N.16°W., 109 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John Powell - 2/4/70 - C.S. File 54/31-45

-----  
Found - Orig. (?)

34" Pine, S.47°W., 48.2'.

30" Fir, N.16°W., 71.9'.

Pine tree opened by myself in 1966, found no scribe. Fir tree has notches & burnt face, probably bark scribed by Byars, it is his trait to put a notch under face. However, there is no evidence of scribing. Cor. monument was a post.

Mark Smalley - For: Kenneth & Hallie Ford - Jan 1995 - M121-57

-----  
New Mon. - 5/8"X48" Iron rod & Aluminum cap mkd. LS 2354 at midpoint of sec. line.

New BT's - 7" fir, N.3°E. 18.6', "¼ S BT"

6" fir, N.27°E. 17', "¼ S BT"

6" fir, N.34°E. 15.7', "¼ S BT"

5" fir, S.74°W. 24.6', "¼ S BT" pistol butt

Bearing & distance to root crown