

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7994)

-----  
Set a Fir post, 3 ft. long, 3" sq., 18" in the ground, for 1/4 sec. cor. mkd. 1/4 S on N. face, from which  
A Cedar 28" dia., bears N .20°W., 24 lks. dist. mkd. 1/4 S BT.  
A Fir 8" dia., bears S.22°W., 34 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - Vernon Tracy, Mike Darby, Jack Barnett, crew - Sept. 1964 - C.S. File 52/25-23

-----  
Found - 3/4" I.Pipe and both original BTs.  
28" Cedar, now 39" N.20°W., 15.8 ft., shows "1/4S", bark scribe.  
8" W.Fir, now 24" S.22°W., 22.4 ft., opened and shows "4S" scribe.

Set Brass cap with other pipe alongside at cor. marked:  
County Surveyors Office  
T 31 S R 6 W  
1/4 S 21  
S 28  
1964

New BTs -9" D.Fir S.7°W., 35.9 ft. mkd. 1/4 S28 CS BT.  
12" D.Fir N.59°W., 27.5 ft. mkd. 1/4 S21 CS BT.

Note: See corner notes for W.C. - I.D. #338300

Mark Smalley - For:Kenneth & Hallie Ford - Jan 1995 - M121-57

-----  
Set 1 1/2"x24" Drill steel 6" under surface of road at rec. dist from BT & WC.  
Found BT's - 16" Fir, N.59°W., 27.5' scribe visible  
Mon. Found - 1964 County brass cap & iron pipe  
Witness corner 150' west on line  
WC BT's Fd.- 19" Fir, N.49°E. 27.4' healed  
14" Fir, S.32°E. 9.4' healed

Fd. & used on BLM dependent resurvey by A. Bert Skeesick & Timothy Moore, Cadastral Surveyors under Group #1950, surveyed April/May 2000 (DCSO rec. Vol. 53 Page"(s) 20669