

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7997)

-----  
Set a Fir post, 3 ft. long, 3" s., 18" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which  
A Laurel 8" dia., bears N.72°E., 14 lks. dist. mkd. ¼ S BT  
A Laurel 6" dia., bears S.55°W., 28 lks. dist. mkd. ¼ S BT

Survey by Bruce Shaner L.S. #430 - For: C & D Lumber Co. - June 1980 - RM 3-32

-----  
Set Brass cap mkd. "T31S R6W W.M. S S9 S16 RLS 430 1980"  
BTs - 40" D.Fir bears N.59°W., 16.0 ft. scribed ¼S S9 BT.  
5" Madrone bears S.6°W., 21.4 ft. scribed ¼S S16 BT.  
42" D.Fir bears S.26°E., 18.4 ft. scribed ¼S S16 BT.

Cor. Fd. and used in BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17304)