

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7999)

-----  
Set a post, 3 ft. long, 3" sq., 18" in the ground for 1/4 sec.cor. mkd. 1/4 S on N. face, from which  
A Laurel 18" dia., bears S.20°W., 8 lks. dist.mkd. 1/4 S BT.  
A Fir 12" dia., bears N.25°W., 27 lks. dist. mkd. 1/4 S BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17307)

-----  
Point for the 1/4 sec. cor. at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked T 31 S R 6 W

1/4  $\frac{S \ 4}{S \ 9}$   
1980

from which

A Fir 45" dia., bears N.19 1/2°W., 42 lks. dist. mkd. 1/4 S4 BT  
A Fir 19" dia., bears S.1 1/2°W., 28 lks. dist. mkd. 1/4 S9 BT.

Kris DeGroot - For: Silver Butte Timber Co. - Jan 2004 - M 137-77

-----  
Found - 2 1/2" USBLM standard brass capped iron post by Jelly, & Rogers USBLM in 1965, firmly set projecting 4" above the ground, (properly) marked.

From which BTs my Jelly & Rogers in 1980:

A 46" D.Fir bears N.22°05'W., 27.9 ft. with healed blaze (rec. S.19 1/2°W., 42 lks.)

A 26" D.Fir bears N.0°45'W., 17.9 ft. with healed blaze (rec. S.1 1/2°W., 28 lks.)

New BTs- A 17" D.Fir bears N.21°E., 48.7 ft. scribed "1/4 S4 BT"

A 12" D.Fir bears S.84°35'E., 23.3 ft. scribed "1/4 S9 BT"