

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; 3 & 4, T32-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - George W. Hyde under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 19 Page(s) 7948)

-----  
Set post cor. to secs. 3, 4, 33 and 34, from which  
A Fir 40" dia., bears N.72°E., 72 lks. dist.  
A Fir 36" dia., bears S.25°E., 62 lks. dist.  
A Fir 30" dia., bears S.4°W., 76 lks. dist.  
A Fir 34" dia., bears N.59°W., 73 lks. dist.

Survey by Ronald Quimby, L.S. #1654 - For: Roseburg Lumber Co. - March 1980 - M 79-25

-----  
Set Brass cap stamped:            T 31 S    R  
  S 33 S 34 6 1980 RLS 1005  
  S 4 S 5 W  
  T 32 S

BTs - 16" Fir bears S.26°E., 4.7 ft. scribed S3 T32S R6W  
      12" Fir bears N.54°E., 8.7 ft. scribed S34 T31 R6W  
      14" Fir bears N.68°W., 8.1 ft. scribed S33 T31 R6W  
      12" Fir bears S.42°W., 14.9 ft. scribed S4 T32 R6W

Four original BTs, four BTs mkd. by Quimby and 1980 cap Fd. and used in BLM resurvey by Mark Dixon and Henry Hartley, under Group #1337, surveyed July/Sept. 1989 (DCSO records, Vol. 48 Pgs. 18564-65)