

PRIMARY CORNER DESCRIPTION Sec Cor for 21, 22, 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7983)

-----  
Set Cedar post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs.21, 22, 27 and 28 mkd. T31SR6W S22 on NE.; S27 on SE.; S28 on SW.; and S21 on NW. faces, with 3 notches on E. and 2 notches on S. edges, from which  
A Pine 60" dia., bears N.36°E., 70 lks. dist. mkd. T31S R6W S22 BT.  
A Fir 15" dia., bears S.45°E., 13 lks. dist. mkd. T31S R6W S27 BT.  
A Pine 30" dia., bears S.33°W., 97 lks. dist. mkd. T31S R6W S28 BT.  
A Cedar 16" dia., bears N.44°W., 48 lks. dist. mkd. T31S R6W S21 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Mike Darby, Jack Barnett - Sept. 1964 - C.S. File 52/25-22

-----  
Found - 16" Cedar N.44°W., 31.7 ft. now 30", chopped out and face rotted, alive.  
15" Fir S.45°E., 8.6 ft. rotted stump, shows "27W" bark scribed.  
NE and SW BTs are down, burned and rotting. No scribe found.

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 6 W  
S 21 | S 22  
S 26 | S 27  
1964

New BTs -8" W.Fir S.56°E., 32.7 ft. mkd. T31S R6W S27 CSBT.  
12" W.Fir N.75°E., 40.5 ft. mkd. T31S R6W S22 CSBT  
14" D.Fir S.72°W., 17.2 ft. mkd. T31S R6W S28 CSBT  
8" W.Fir N.15°W., 30.0 ft. mkd. T31S R6W S21 CS BT

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17297)

-----  
The Sec. cor., perpetuated by Tracy in 1964, as described in a Douglas County Surveyor's record, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with brass cap.  
from which the remaining original bearing trees:  
A Cedar 32" dia., bears N.44°W., 48 lks. dist., no scribe marks visible on opened blaze.  
and the remains of bearing trees mkd. by Tracy:  
(Cont. Next Page)

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec Cor for 21, 22, 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir 16" dia., bears S.70°W., 26 lks. dist., with a healed blaze.

A Grand Fir snag 16" dia., bears N.15°W., 45½ lks. dist., with scribe marks T31S R6W S21 CS BT visible on open blaze.

and new bearing trees:

A Fir 18" dia., bears N.37°E., 61 lks. dist. mkd. T31S R6W S22 BT.

A Fir 30" dia., bears S.1½°E., 103 lks. dist. mkd. T31S R6W S27 BT.

Mark Smalley - For:Kenneth & Hallie Ford - Jan 1995 - M121-57  
-----

Found - 1964 Brass cap & Iron pipe  
30" cedar N.44°W. 31.7' rotten center original  
15" fir, S.56°E. 32.7' stump  
19" fir, S.72°W. 17.2' scribe visible  
30" fir, South 58' stump not of record visible  
scribe

New BT's-7" fir, S.31°E. 52.5' "S 27 BT"  
17" fir, N.10°W. 39' "S 21 BT"

Fd. & used on BLM dependent resurvey by A. Bert Skeesick & Timothy Moore, Cadastral Surveyors under Group #1950, surveyed April/May 2000 (DCSO rec. Vol. 53 Page"(s) 20668-9