

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7984)

-----  
Set Laurel post 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor. mkd. ¼ S on W. face, from which

A Laurel 12" dia., bears S.73°W., 76 lks. dist. mkd. ¼ S  
BT

A Laurel 12" dia., bears N.40°E., 98 lks. dist. mkd. ¼ S  
BT.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17298)

-----  
Point for the ¼ sec.cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 31 S R 6 W

1/4

S 21 S 22

1980

from which

A Fir 10" dia., bears S.68°E., 8½ lks. dist. mkd. ¼ S22 BT

A Fir 8" dia., bears N.65½°W., 40 lks. dist. mkd. ¼ S21 BT

Found OK by Lang, April 1995 - M125-3