

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7986)

A Laurel tree, 6" dia., which I mkd. $\frac{1}{4}$ S on W. face, for $\frac{1}{4}$ sec. cor., from which

A Fir 36" dia., bears N.20°E., 49 lks. dist. mkd. $\frac{1}{4}$ S BT.

A Fir 18" dia., bears S.18°W., 30 lks. dist. mkd. $\frac{1}{4}$ S BT.

Survey by Bruce A. Shaner, L.S. #430 - For: C & D Lumber Co. June 1980 - RM 3-32

Set Brass cap mkd. "T31S R6W W.M. 1/4S S16 S15 RLS 430 1980" BTs - 28" D.Fir bears S.18°W., 19.8 ft. to face scribed " $\frac{1}{4}$ S S16 BT"

36" D.Fir, orig. BT snag, bears N.20°E., 32.3 ft. to face.

30" D.Fir bears S.8°E., 28.8 ft. to center scribed " $\frac{1}{4}$ S S15 BT"

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2300, Surveyed March/April 2008 - (DCSO records Vol. 56 Page(s) 22175)

The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, perpetuated by Shaner, in 1980, monumented with an iron post, 2 $\frac{1}{2}$ " dia., firmly set, projecting 5" above the ground, with brass cap (properly) mkd from which the remains of the original bearing trees

A fir snag, 35" dia., bears N.20°E., 32.3 ft., with no marks visible.

A fir, 29" dia., bears S.18°W., 19.8 ft., with scribe marks $\frac{1}{4}$ S S16 BT visible on the bark.

and the remains of a bearing tree mkd. by Shaner

A fir snag, 30" dia., bears S.10 $\frac{1}{4}$ °E., 28.1 ft., with scribe marks $\frac{1}{4}$ S S15 BT visible on the bark.

and a new bearing tree

A fir, 7" dia., bears N.61 $\frac{3}{4}$ °E., 12.7 ft., mkd. $\frac{1}{4}$ S15 BT.

Corner is located 50 ft. S. of a spur, slopes E.