

TOWNSHIP 31 RANGE 06 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - W.H. Byars, under contract # 448 survey dated June 13, 1882 (DCSO records Vol. 19 Page(s) 7987-88)

Set a Laurel post, 3 ft. long, 3" sq., 18" in the ground for 1/4 sec. cor. mkd. 1/4 S on W. face, from which
A Fir 30" dia., bears N.70°E., 16 lks. dist. mkd. 1/4 S BT
A Fir 16" dia., bears S.88°W., 44 lks. dist. mkd. 1/4 S BT

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1042, surveyed Oct. 1980/Oct. 1981 (DCSO records Vol. 45 Page(s) 17302)

Point for the 1/4 sec. cor. at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
T 31 S R 6 W
1/4
S 9 | S 10
1980

from which
A Fir 5" dia., bears S.54 1/2°E., 45 lks. dist. mkd. 1/4 S10 BT
A Fir 8" dia., bears S.17°W., 24 lks. dist. mkd. 1/4 S9 BT.

Fd. Ok by K. DeGroot, May 2004 - M146-5